

Productspecificatie / Technical specification / Technische Daten

Yukon

Artikelnummer / Article number / Artikelnummer	0486
Constructie / Construction / Herstellungsverfahren	1/10" cut pile
Aantal kleuren / Number of colours / Lieferbare Farben	16
Verfmethode / Dyeing method / Färbung	Solution dyed
Breedte / Width / Breite	400 cm
Poolmateriaal / Pile material / Polnutzschicht	100% Invista BCF PA SDN 6.6
Poolgewicht / Pile weight / Poleinsatzgewicht	± 1150 g/m ²
Totaalgewicht / Total weight / Gesamtgewicht	± 2015 g/m ²
Poolhoogte / Pile height / Polhöhe	± 6.8 mm
Totaalhoogte / Total height / Gesamthöhe	± 9.6 mm
Pooldichtheid / Pile density / Polrohdichte	0.124 g/cm ³
Aantal noppen / Tuft density / Noppenanzahl	172.000/m ²
Draagdoek / Primary backing / Grundgewebe	Woven PP
Rug / Secondary backing / Rückenausstattung	Actionbac
Extra / Extra / Extra	Bleach resistant
Brandgedrag / Flammability / Brennverhalten	Bfl-S1
Lichtechtheid / Fastness to light / Lichtechtheit	>5
Wrijftechtheid / Fastness to rubbing / Reibecktheit	>4
Waterechtheid / Fastness to water / Wasserechtheit	>4 (colour change)
Warmteweerstand / Thermal resistance / Wärmedurchlasswiderstand	0.130 m ² K/W
Geluidsisolatie / Impact noise rating / Trittschallschutz	N/A
Geluidsabsorptie / Soundabsorption / Schallabsorptionsgrad	N/A
Persoonsoplading / Static electrical charging / Elektrische Aufladung	<2.0 kV
Oppervlakteweerstand / Surface resistance / Oberflächenwiderstand	N/A
Gebruiksklasse / Intensity of use / Strapazierwert	23 / 33
Comfortklasse / Luxury rating/ Komfortwert	LC 5
Gebruik op trappen / Suitability for stairs / Treppenprüfung	A, continuous
Gebruik met zwenkwielen / Suitability for castor chairs / Stuhlrollenprüfung	A, continuous
Verpakking / Packing / Packing	Roll & cut length



EN 14041



17

DOP: 1013-124459
Belakos Flooring BV
De Blokmat 15
8281 JH Genemuiden
EN 1307



Textile Floor Covering

